

PRODUCT-DETAILS

03700380

600A 1H AL COMPR LUG 700 STR 900SOL



General Information	
Extended Product Type	03700380
Product ID	7TAA122010R0028
EAN	0783786655922
Catalog Description	600A 1H AL COMPR LUG 700 STR 900SOL
Long Description	15/25/35kV 600 Amp Series Deadbreak Compression Lug (Tin-Plated Aluminum). Conductor Size kcmil Compressed/Stranded 700/750 or Compacted/Solid 900. Length 5.94 inches. Diameter 1.38 Inches. 1-Hole Pad, .50 inch Thick. Hole Size .688 inch Diameter.

Ordering	
EAN	0783786655922
UPC	783786655922
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information		
Package Level 1 Units	25 piece	
Package Level 1 Width	9.7 in 246 mm	
Package Level 1 Height	8.3 in 211 mm	

Package Level 1 Depth / 13 in Length 330 mm

Additional Information	
Application	Used with 15/25/35kV 600 Amp Deadbreak Elbow and Splice products.
Brand / Label	Elastimold
Cable Size	700 to 750 kcmil 900 kcmil
Color	Silver
Connection Type	Compression
Current Rating	600 A
Effective Date	19980115
Insulation Material	None
Material	Aluminum
Product Name	"ELECTRICAL CONNECTOR,>1000V"
Product Type	Compression Lug
Size	Length 5.94 inch, Diameter 1.38 inch, Hole .688 inch Diameter.
Special Functions	Tin Plated Aluminum. Hole Size .688 inch. Connectors can used with both Copper and Aluminum Conductors.
Voltage Rating	15 to 35 kV

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	03700380	
Instructions and Manuals	03700380	

Classifications	
ETIM 6	EC001053 - Crimp cable lug for aluminium conductors
ETIM 7	EC001053 - Crimp cable lug for aluminium conductors
ETIM 8	EC001053 - Crimp cable lug for aluminium conductors
UNSPSC	39121405
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4532 >> Cable or wire lug

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Cable\ Accessories\ and\ Apparatus\ \rightarrow\ Cable\ Accessories$

03700380 3

